

Series 25KS Safety Lock



Page Tech Sheet 519

Working Temperature :
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 35 bar (500 PSI)



Actual Size

Interchangeability:
Rectus design


Material:
Brass nickel plated, Buna seal
(standard series coupling)
Application:
Two-handed disconnection prevents accidental disconnection. The coupling and plug must firstly be pushed together before the sleeve is pulled back.

Couplings




Male Thread, BSPT

2510				
25KSAK13SPN	1/4"	19	60	74.70
25KSAK17SPN	3/8"	19	60	74.70
25KSAK21SPN	1/2"	22	61	76.50



Female Thread, BSPP

2510				
25KSIW13SPN	1/4"	19	56	74.70
25KSIW17SPN	3/8"	19	55	74.70
25KSIW21SPN	1/2"	24	58	76.50



Hose Tail

2510	To Suit Hose I.D.			
25KSTF08SPN	8mm (5/16")	19	74	74.70
25KSTF10SPN	10mm (3/8")	19	74	74.70
25KSTF13SPN	13mm (1/2")	19	74	76.50

Plugs



Male Thread, BSPT

2510				
25SSAK13SXN	1/4"	14	37	11.05
25SSAK17SXN	3/8"	17	37	11.05
25SSAK21SXN	1/2"	22	43	27.70



Female Thread, BSPP

2510				
25SSIW13SXN	1/4"	17	33	11.05
25SSIW17SXN	3/8"	19	33	12.50



Hose Tail

2510	To Suit Hose I.D.		
25SSTF08SXN	8mm (5/16")	48	20.90
25SSTF10SXN	10mm (3/8")	48	21.35
25SSTF13SXN	13mm (1/2")	48	12.10

Other materials, seals and finishes available on request, please contact our technical department for further details.

Hydraulics

Hydraulic Quick Release Couplings

Pneumatic Quick Release Couplings

Air Prep, Media, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns, Vacuum & Nozzles

Pressure Wash, Fuelling & Lubrication

Air Tools & Compressor Equipment

Tools, Hardware & PPE