

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 12 bar (174 PSI)



Material:
Brass, nickel plated,
Buna seal (standard series)
coupling

Application:
General purpose pneumatic coupling
self venting safety feature.
Machinery construction, trade and
automotive

New updated version of the 27KE self venting couplings.
Still interchangeable with original 27 series couplings.



Actual Size

Couplings



Male Thread, BSPT


0194				
1700KEAW17SPN	3/8"	24	67	184.85
1700KEAW21SPN	1/2"	24	70	184.85
1700KEAW26SPN	3/4"	30	74	184.85



Female Thread, BSPP


0194				
1700KEIW17SPN	3/8"	24	64.5	184.85
1700KEIW21SPN	1/2"	24	68	184.85
1700KEIW26SPN	3/4"	32	74	184.85

Plugs



Male Thread, BSPT

2710				
275FAK13SXN	1/4"	17	40	12.40
275FAK17SXN	3/8"	17	40	12.40
275FAK21SXN	1/2"	22	45	13.25
275FAK26SXN	3/4"	27	48	17.35



Female Thread, BSPP

2710				
275FIW13SXN	1/4"	17	33	13.25
275FIW17SXN	3/8"	19	33	13.25
275FIW21SXN	1/2"	24	37	13.25
275FIW26SXN	3/4"	32	42	22.45



Hose Tail

2710	To Suit Hose I.D.		
275FTF06SXN	6mm (1/4")	48	7.75
275FTF09SXN	9mm	48	7.75
275FTF10SXN	10mm (3/8")	48	7.75
275FTF13SXN	13mm (1/2")	48	7.75
275FTF16SXN	16mm (5/8")	48	10.80
275FTF19SXN	19mm (3/4")	48	12.25

Other materials, seals and finishes available on request, please contact our technical department for further details.