

Series 41KF Water Couplings



Page Tech Sheet525

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static
Working Pressure:
PB 35 bar (500 PSI)



Actual Size

Interchangeability:
Rectus27 Cejn 4170

Material:
Steel nickel plated
Application:
Straight through coupling designed for water

Couplings







Male Thread, BSPP

4110			£
41KFAW21MPN	1/2"	31	23.70
41KFAW26MPN	3/4"	32	39.80



Female Thread, BSPP & Metric


4110				
41KFIW21MPN	1/2"	24	32	24.45
41KFIW26MPN	3/4"	30	32	43.65
41KFIM22MPN	M22	24	32	30.10







Hose Tail

4110	To Suit Hose I.D.		£
41KFTF10MPN	10mm (3/8")	48	24.80
41KFTF13MPN	13mm (1/2")	48	24.80
41KFTF16MPN	16mm (5/8")	48	29.35
41KFTF19MPN	19mm (3/4")	48	33.25

Plugs







Male Thread, BSPP

<div>4110</div>				
41SFAW21MXN	1/2"	24	40	17.30
41SFAW26MXN	3/4"	32	45	21.10



Female Thread, BSPP

<div>4110</div>				
41SFIW21MXN	1/2"	24	37	29.35
41SFIW26MXN	3/4"	32	42	33.25



Hose Tail

4110	To Suit Hose I.D.		£
41SFTF10MXN	10mm (3/8")	48	11.10
41SFTF13MXN	13mm (1/2")	48	11.10
41SFTF16MXN	16mm (5/8")	48	15.50
41SFTF19MXN	19mm (3/4")	48	16.55

Other materials, seals and finishes available on request, please contact our technical department for further details.

You might also need...



Wash Down Guns



...on pages 1614-1615