

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
PB 50 bar (725 PSI)



Actual Size

Interchangeability:
Rectus design

Material:
Brass nickel plated
Application:
Robust steel coupling for
compressed air

Hydraulics

Hydraulic Quick Release Couplings

Pneumatic Quick Release Couplings

Air Prep, Media, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns, Vacuum & Nozzles

Pressure Wash, Fuelling & Lubrication

Air Tools & Compressor Equipment

Tools, Hardware & PPE

Couplings



Male Thread, BSPP

0194				
51KBAW13SPN	1/4"	22	61	29.70
51KBAW17SPN	3/8"	22	61	29.70
51KBAW21SPN	1/2"	22	61	29.70



Female Thread, BSPP

0194				
51KBW13SPN	1/4"	22	61	29.70
51KBW17SPN	3/8"	22	61	34.85
51KBW21SPN	1/2"	22	61	30.70



Hose Tail

0194	To Suit Hose I.D., mm			
51KBTF06SPN	6	21	78	30.60
51KBTF09SPN	9	21	78	30.60
51KBTF13SPN	13	21	78	31.15

Plugs



Male Thread, BSPP

0194				
51SFAW13SXN	1/4"	17	35	6.25
51SFAW17SXN	3/8"	19	36	47.30



Female Thread, BSPP

0194				
51SFIW13SXN	1/4"	17	34	8.70
51SFIW17SXN	3/8"	19	34	7.50



Hose Tail

0194	To Suit Hose I.D., mm			
51SBTF06SPN	6	21	65.5	25.10
51SBTF09SPN	9	21	65.5	25.10
51SBTF11SPN	11	21	65.5	25.10
51SBTF13SPN	13	21	65.5	25.10

Other materials, seals and finishes available on request, please contact our technical department for further details.