


Working Temperature:
-20°C to +100°C
Standard seal NBR



Maximum Static
Working Pressure:
PB 35 bar (500 PSI)

Interchangeability:
Rectus design

Material:
Brass nickel plated, Buna seal
Application:
Robust steel coupling for
compressed air



Couplings



Male Thread, BSPP

0194				£
57KBAW26SPN	3/4"	34	100	132.90
57KBAW33SPN	1"	41	100	134.70

Female Thread, BSPP

0194				£
57KBIW21SPN	1/2"	34	100	132.95
57KBIW26SPN	3/4"	34	100	132.95
57KBIW33SPN	1"	41	101	134.70

Actual Size



Hose Tail

0194	To Suit Hose I.D. mm			£
57KBTF16SPN	16	34	122	136.30
57KBTF19SPN	19	34	122	137.55

Plugs



Male Thread, BSPP

0194				£
57SBAW17SPN	3/8"	27	86	87.80
57SBAW21SPN	1/2"	27	83	87.80
57SBAW26SPN	3/4"	34	85	90.30
57SBAW33SPN	1"	41	85	92.10

Female Thread, BSPP

0194				£
57SBIW21SPN	1/2"	27	85	90.30
57SBIW26SPN	3/4"	34	85	90.30

Hose Tail

0194	To Suit Hose I.D. mm			£
57SBTF13SPN	13	34	107	93.70
57SBTF19SPN	19	34	107	95.10

Other materials, seals and finishes available on request, please contact our technical department for further details.