

Series 68KA



Working Temperature:
-10°C to +80°C
Standard seal NBR

Maximum Static Working Pressure:
PB 17 bar (246 PSI)

Single Shut Off

Interchangeability:
Schrader heavy duty

Material:
Steel nickel plated, Buna seal
(standard series coupling)

Application:
General purpose pneumatic coupling




Actual Size

Couplings




Male Thread, BSPP

1710				£
68KAAW17SPN	3/8"	30	66	45.35
68KAAW21SPN	1/2"	30	68	45.35
68KAAW26SPN	3/4"	30	68	51.10



Female Thread, BSPP

1710				£
68KAIW13SPN	1/4"	30	74	44.00
68KAIW17SPN	3/8"	30	74	66.25
68KAIW21SPN	1/2"	30	68	46.65
68KAIW26SPN	3/4"	32	68	51.10



Hose Tail

1710	To Suit Hose I.D.			£
68KATF10SPN	10mm (3/8")	30	81	65.70
68KATF13SPN	13mm (1/2")	30	81	51.50
68KATF19SPN	19mm (3/4")	30	81	51.50

Plugs



Male Thread, BSPT

1710				£
68SFAK13SXN	1/4"	17	48	7.35
68SFAK17SXN	3/8"	22	50	7.35
68SFAK21SXN	1/2"	22	52	7.50
68SAFW26SXN	3/4"	27	53	7.35



Female Thread, BSPT

1710				£
68SFIW13SXN	1/4"	18	43	7.35
68SFIW17SXN	3/8"	22	46	7.35



Hose Tail

1710	To Suit Hose I.D.			
68SFTF10SXN	10mm (3/8")	71	7.35	
68SFTF13SXN	13mm (1/2")	67	7.35	

Other materials, seals and finishes available on request, please contact our technical department for further details.