




Mold Series



 Working Temperature:
-15°C to +200°C
Standard seal FKM

 Maximum Static Working Pressure:
PB 15 bar (217 PSI)
Safety Factor of 4 to 1




Actual Size

Material:
Brass

Application:
Mold coupling

Couplings



Straight Hose Tail, 9mm Profile, Valved


0194	To Suit Hose I.D.	£
2053-5613	9mm (3/8")	18.55

Straight Hose Tail, 13mm Profile, Non-valved

0194	To Suit Hose I.D.	£
2053-5621	13mm (1/2")	23.00


Straight Hose Tail, 13mm Profile, Valved

0194	To Suit Hose I.D.	£
2053-5639	13mm (1/2")	21.55



45° Tail, 13mm Profile, Non-valved

0194	To Suit Hose I.D.	£
2053-5662	13mm (1/2")	32.90



90° Hose Tail, 9mm Profile, Valved

0194	To Suit Hose I.D.	£
2053-5696	9mm (3/8")	27.55


90° Tail, 13mm Profile, Valved

0194	To Suit Hose I.D.	£
2053-5712	13mm (1/2")	28.85


Non-valved, Straight Through Plugs



Male Thread BSPT, 9mm Profile

0194		£
2053-5746	1/8"	1.75
2053-5753	1/4"	1.75

Male Thread BSPT, 13mm Profile

0194		£
2053-5761	1/4"	1.90
2053-5779	3/8"	7.45

Valved Shut-off Plug



Male Thread BSPT, 9mm Profile

0194		£
2053-5787	1/4"	8.70

Male Thread BSPT, 13mm Profile

0194		£
2053-5795	3/8"	9.10

For...




Ambersil Moulding Range

...see page 1567

Other materials, seals and finishes available on request, please contact our technical department for further details.

- Hydraulics
- Hydraulic Quick Release Couplings
- Pneumatic Quick Release Couplings
- Air Prep, Media, Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns, Vacuum & Nozzles
- Pressure Wash, Fuelling & Lubrication
- Air Tools & Compressor Equipment
- Tools, Hardware & PPE