Hydraulics

& Test KELM™

Pneumatics Pneumatic & Vacuum

Equipment

Ring Main

Systems

Adaptors & Fittings Stainless Steel Malleable

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Air Tools & Compressor Equipment

## Series 86KA & Accessories







### Page Tech Sheet 527




Working Temperature: -15°C to +200°C Standard seal FKM



Maximum Static Working Pressure: PB 15 bar (217 PSI)





Double Shut Off







**Actual Size** 

# Interchangeability:

D-M-E, Foster FJT, Parker Mold Mate Material:

Brass, seals Viton standard, silicone available

Application:

Brass coupling for connection of coolant lines to moulds and dies

## Couplings





Male Thread, BSPP, Non-valved

4610

86KFAW13MVX 1/4"

£ 15 43 20.35

Male Thread, BSPP, Valved

4610

86KBAW13MVX 1/4"







4610	<b>{ }</b>	mm	L mm'	$\mathfrak{L}$
86KFIW10MVX	1/8"	15	39	17.50
86KFIW13MVX	1/4"	15	41	17.50

#### Female Thread, BSPP, Valved

4610

86KBIW13MVX











4610



#### Straight Hose Tail, Valved

4610	To Suit Hose I.D.	mm	L mm	$\mathfrak{L}$
86KBTF06MVX	6mm (1/4")	15	56	24.45
86KBTF09MVX	9mm (3/8")	15	56	24.45



(mm)

15

#### 45° Hose Tail, Non-valved

4610

To Suit Hose I.D.

L £

86KFTH08MVX 8mm (5/16") 15 61 22.85

#### 45° Hose Tail, Valved

Blow Guns, Vacuum & Nozzles Pressure Wash, Fuelling & Lubrication

To Suit 4610 Hose I.D. 86KBTH09MVX 9mm (3/8")









4610

86KFTR09MVX



To Suit Hose LD.

9mm (3/8")





L

44



22.85



90° Hose Tail, Non-valved

86KBTR09MVX



15



Other materials, seals and finishes available on request, please contact our technical department for further details.

