

Series 1300



Tech Sheet 530

Working Temperature:
-20°C to +100°C
Standard seal NBR

Maximum Static Working Pressure:
35 bar



Features:

- Single hand operation

Material:

Coupling: Brass nickel plated and chrome plated

Plug: Steel zinc plated

Seals: NBR

Interchangeability:

Rectus series 31 and Cejn 303

Application:

Series 1300 is used mainly for applications in the area of compressed air and liquids. Optimally suited to smaller to medium-sized pneumatic systems and to compressed air tools. The coupling series stands out for its compact design and high flow rates with the UltraFlo valve. Coupling body made of nitrocarburized steel.



Actual Size

Couplings



BSPP, Valved Nitrile Seals

0073		Thread	L mm	£
TE-1300		G1/4 Female	49	24.95
TE-1300 A		G3/8 Male	49	24.95
TE-1300 B		G3/8 Female	50	24.95

BSPP, Valved Viton Seals

0073		Thread	L mm	£
TE-1300 V		G1/4 Female	49	62.45

Plugs



BSPP

0073		Thread	L mm	£
TE-13110		G1/8 Male	35	6.05
TE-13210		G1/4 Male	38	9.50
TE-13220		G3/8 Male	38	8.15
TE-13410		G1/4 Female	36	6.05

Dust Protection



Plug

0073	To Suit	£
TE-1325	Series 1300	4.35

Hose Tail

0073	To Suit Hose I.D. mm	L mm	£
TE-13006	6	44	6.55
TE-13010	10	44	7.00
TE-13012	12	47	5.90

Other materials, seals and finishes available on request, please contact our technical department for further details.