

Air Line Couplings

Mini Couplings

Working Temperature:
-20°C to +80°C

Maximum Working Pressure:
35 bar (508 psi)

Nominal Bore: 5.0mm
Flow rate @ 6 bar (0.5 bar P.D.)
560 l/min

Interchangeability:
Camozzi Mini, Cejn 50, Legris 21, Norgren 233,
Rectus 21 and Schrader Mini



Male Thread, BSPP

7000		£
AC11AM	1/8"	14.75
AC11CM	1/4"	14.75



Female Thread, BSPP


7000		£
AC11AF	1/8"	14.75
AC11CF	1/4"	14.75



Hose Tail

7000	To Suit Hose I.D.	£
AC1106	6mm (1/4")	17.25
AC1108	8mm (5/16")	17.25
AC1109	9mm	17.25

Mini Plugs



Male Thread, BSPP

7000		£
AA11AM	1/8"	3.55
AA11CM	1/4"	3.55



Female Thread, BSPP

7000		£
AA11AF	1/8"	3.55
AA11CF	1/4"	3.55



Hose Tail

7000	To Suit Hose I.D.	£
AA1106	6mm (1/4")	3.55
AA1109	9mm	3.55

Hydraulics

Hydraulic Quick Release Couplings

Pneumatic Quick Release Couplings

Air Prep, Media, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns, Vacuum & Nozzles

Pressure Wash, Fuelling & Lubrication

Air Tools & Compressor Equipment

Tools, Hardware & PPE