

EC116

Applications:

- High pressure cleaners for food, car wash, labour and swimming bath areas
- For use with TCC series fittings

Construction:

- Synthetic rubber tube
- One-wire braid reinforcement
- Smooth synthetic rubber cover



Working Temperature:
-40°C to +150°C
(intermittent)



Per Metre

0235	ID	OD mm	bar	£
EC116-04	1/4"	13	250	6.60
EC116-05	5/16"	14.4	250	6.70
EC116-06	3/8"	16.3	250	7.20
EC116-08	1/2"	19.8	250	8.35

EC216

Applications:

- High pressure cleaners for food, car wash, labour and swimming bath areas
- For use with TCC series fittings

Construction:

- Synthetic rubber tube
- Two-wire braid reinforcement
- Smooth synthetic rubber cover



Working Temperature:
-40°C to +150°C
(intermittent)



Per Metre

0235	ID	OD mm	bar	£
EC216-04	1/4"	14.2	400	8.10
EC216-05	5/16"	15.8	400	8.35
EC216-06	3/8"	18	400	9.25
EC216-08	1/2"	21.5	400	10.95

FC611

Features

- Requires no skiving of hose
- High pressure performance up to 5,000 psi operating pressure
- Specifically developed for use with the following phosphate ester fluids:
 - Skydrol LD4
 - Skydrol 500B
 - Hyjet IVA Plus

Benefits

- Meets most operating pressure requirements of GSE systems
- Helps provide longer service life in the typical GSE operating temperature ranges
- EPDM hose can be selected from three construction choices:
 - FC611 one wire braid and FC693 two wire braid constructions for use with TTC (Through-The-Cover) fittings
 - FC636 four spiral wire construction for use with four wire spiral 4s fittings



Working Temperature:
-40°F to +175°F

Tech Sheet
68204



Per Metre

0235	ID	OD mm	bar	£
FC611-08TD	1/2"	20.32	137	24.70
FC611-12TD	3/4"	27.94	86	27.45
FC611-16TD	1"	35.81	69	67.00
FC611-20TD	1.1/4"	43.43	43	73.75
FC611-24TD	1.1/2"	50.55	34	114.20
FC611-32TD	2"	64	25	192.60

FC693

Per Metre

0235	ID	OD mm	bar	£
FC693-04	1/4"	15	344	29.10
FC693-06	3/8"	19.5	127	22.70
FC693-08	1/2"	22.1	241	36.55

