

Actuated Process Ball Valves

Actuator Working Temperature:
-20°C to +80°C
Ball Valve Working Temperature:
-20°C to +95°C

Actuator Working Pressure:
2.5 to 8 bar
Ball Valve Maximum Working Pressure:
3/8" 16 bar
1/2" to 2" 40 bar

Actuator Media:
Dry or lubricated compressed air, to be filtered by a 30 µm filter element
Travel Adjustment: ±5° on the rotation 0° and 90°

Ball Valve Full Bore

Nickel Plated Brass Body Ball Valves

Tech Sheet 10145



Double Acting, Aluminium Actuator, BSPP

2184-0000		3/8"	108.35
2184-0001		1/2"	112.30
2184-0002		3/4"	125.35
2184-0003		1"	144.95
2184-0004		1.1/4"	197.10
2184-0005		1.1/2"	271.25
2184-0006		2"	356.05

Nickel Plated Brass Body Ball Valves, WRAS Approved

Tech Sheet 10147



WRAS
APPROVED PRODUCT

Double Acting, Aluminium Actuator, BSPP

2184-0014		1/2"	112.30
2184-0015		3/4"	125.35
2184-0016		1"	144.95
2184-0017		1.1/4"	197.10
2184-0018		1.1/2"	290.90
2184-0019		2"	375.80

- Hydraulics
- Hydraulic Quick Release Couplings
- Pneumatic Quick Release Couplings
- Air Prep., Media, Monitor & Test
- KELMK™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns, Vacuum & Nozzles
- Pressure Wash, Fuelling & Lubrication
- Air Tools & Compressor Equipment
- Tools, Hardware & PPE

Tech Sheet 10146



Single Acting, Aluminium Actuator, BSPP

2184-0007		3/8"	181.85
2184-0008		1/2"	185.85
2184-0009		3/4"	198.90
2184-0010		1"	218.50
2184-0011		1.1/4"	270.70
2184-0012		1.1/2"	388.55
2184-0013		2"	473.45

Tech Sheet 10148



WRAS
APPROVED PRODUCT

Single Acting, Aluminium Actuator, BSPP

2184-0020		1/2"	185.85
2184-0021		3/4"	198.90
2184-0022		1"	218.50
2184-0023		1.1/4"	270.70
2184-0024		1.1/2"	388.55
2184-0025		2"	473.45