# Pneumatic Valves

AIRCOMP STAMPOTECNICA

Page Tech Sheet60398

## 128 Series Pneumatic Valves

General Features:
Construction: Spool-type
Body Size: 22mm
Body Material: Aluminium
Single Use: Yes
Manifold Use: Yes

Working Temperature: -50°C to +50°C

Working Pressure: 1 bar to 10 bar

Coils not included

### 1/4" Solenoid Valve

| 0018 | Function | ISO SYMBOL | £ |
|---|---|---|---|
| 1282133001 | 3/2 Single Solenoid, Spring + Air Return Normally Closed | | 68.70 |
| 1282133002 | 3/2 Single Solenoid, Spring + Air Return Normally Open | | 70.80 |
| 1282133003 | 3/2 Double Solenoid | | 107.25 |
| 1282135001 | 5/2 Single Solenoid, Spring + Air Return | | 72.85 |
| 1282136001 | 5/3 Double Solenoid, Spring to Closed Centre | | 148.40 |

### 1/4" Pilot Valve

| 0018 | Function | ISO SYMBOL | £ |
|---|---|---|---|
| 1282233001 | 3/2 Single Pilot, Spring + Air Return Normally Closed | | 45.35 |
| 1282233002 | 3/2 Single Pilot, Spring + Air Return Normally Open | | 47.60 |
| 1282233003 | 3/2 Double Pilot | | 52.25 |
| 1282235001 | 5/2 Single Pilot, Spring + Air Return | | 52.25 |
| 1282235002 | 5/2 Double Pilot | | 57.75 |
| 1282236001 | 5/3 Double Pilot, Spring to Closed Centre | | 96.15 |

For coils and connectors, see page 715

Other specification models available, please enquire.

You might also need…

SANHA®

NiroSan ® Stainless Steel Press Fit Piping System

…on pages 954-956