

# Directional Control Valves



## Tech Sheet 10313

### Solenoid Coils for Electro Pneumatically Operated Valves

- Solenoid DIN Connector use Form B.

#### U70 Solenoid Coils

| 0158 |                    |       | £ |
|------|--------------------|-------|---|
| U7H  | 24V 50/60Hz 3.5VA  | 15.95 |   |
| U7K  | 110V 50/60Hz 3.5VA | 15.95 |   |
| U7J  | 240V 50/60Hz 4VA   | 15.95 |   |
| U77  | 24V DC 3W          | 15.95 |   |
| U71  | 6V DC 5W           | 16.10 |   |
| U72  | 12V DC 5W          | 15.95 |   |
| U73  | 24V DC 5W          | 15.95 |   |
| U74  | 48V DC 5W          | 15.95 |   |
| U76  | 110V DC 5W         | 15.95 |   |

- Solenoid DIN Connector use Form B.

#### G70 Solenoid Coils

| 0158 |                    |       | £ |
|------|--------------------|-------|---|
| G7H  | 24V 50/60Hz 3.5VA  | 13.80 |   |
| G7K  | 110V 50/60Hz 3.5VA | 13.80 |   |
| G7J  | 240V 50/60Hz 4VA   | 13.80 |   |
| G79  | 48V DC 3W          | 13.80 |   |
| G77  | 24V DC 3W          | 13.80 |   |
| G72  | 12V DC 5W          | 13.80 |   |
| G73  | 24V DC 5W          | 13.80 |   |
| G76  | 110V DC 4W         | 14.35 |   |

- Solenoid DIN Connector use Form A.

#### A80 Solenoid Coils

| 0158 |                  |       | £ |
|------|------------------|-------|---|
| A8B  | 24V 50/60Hz 5VA  | 23.70 |   |
| A8D  | 110V 50/60Hz 5VA | 23.70 |   |
| A8E  | 220V 50/60Hz 5VA | 23.70 |   |
| A83  | 24V DC 4W        | 23.70 |   |
| A84  | 48V DC 4W        | 24.65 |   |
| A86  | 110V DC 4W       | 23.70 |   |

- Solenoid DIN Connector use Form B.

#### G80 Solenoid Coils

| 0158 |          |       | £ |
|------|----------|-------|---|
| G93  | 24V Coil | 53.00 |   |

### Solenoid DIN Connectors



#### Black Connectors

| 0158       | Type                    | £    |
|------------|-------------------------|------|
| KA132000B9 | Form A 18mm Pin Spacing | 2.10 |
| KB132000B9 | Form B 11mm Pin Spacing | 2.10 |



#### Grey Connector

| 0158       | Type                    | £    |
|------------|-------------------------|------|
| KA132000A9 | Form A 18mm Pin Spacing | 2.05 |




#### Transparent Connectors

| 0158       | Type                          | £     |
|------------|-------------------------------|-------|
| KA132V54T9 | Form A 18mm Pin Spacing, 24V  | 11.10 |
| KA132V55T9 | Form A 18mm Pin Spacing, 115V | 11.10 |
| KA132V56T9 | Form A 18mm Pin Spacing, 230V | 11.10 |
| KB132V54T9 | Form B 11mm Pin Spacing, 24V  | 11.10 |
| KB132V55T9 | Form B 11mm Pin Spacing, 115V | 11.10 |
| KB132V56T9 | Form B 11mm Pin Spacing, 230V | 11.10 |


## Tech Sheet 1847

### Series 3, In-line Pneumatically Operated Valves




#### 3/2 Pneumatic/Spring N/C

| 0158     |       | £     |
|----------|-------|-------|
| 338 035  | G1/8" | 40.05 |
| 338L 035 | G1/8" | 40.05 |
| 334 035  | G1/4" | 67.70 |



#### 3/2 Pneumatic/Pneumatic Bistable

| 0158     |       | £     |
|----------|-------|-------|
| 338 033  | G1/8" | 44.50 |
| 338L 033 | G1/8" | 44.50 |
| 334 033  | G1/4" | 67.70 |



#### Series 3, 5/2 Pneumatic/Spring Monostable

| 0158    |       | £     |
|---------|-------|-------|
| 358 035 | G1/8" | 42.40 |
| 354 035 | G1/4" | 71.85 |

Hydraulics

Hydraulic Quick Release Couplings

Pneumatic Quick Release Couplings

Air Prep., Media, Monitor & Test

KELM™ Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main Systems

Adaptors & Fittings

Stainless Steel

Malleable Iron

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns, Vacuum & Nozzles

Pressure Wash, Fuelling & Lubrication

Air Tools & Compressor Equipment

Tools, Hardware & PPE