

3CH0 SAE 100R7 Thermoplastic Hose

Meets or Exceeds:

- Synflex 3CH0
- SAE 100R7

Construction:

- Black polyurethane cover
- Braided synthetic fibre reinforcement
- Nylon core tube

Working Temperature:
-40°C to +100°C
(or to +66°C maximum with water based or fire resistant fluids)



Single Line, 75 Metre Continuous Coils

0235			Die Ref.		£
3CH0-03	3/16"	10	-	207	656.70
3CH0-04	1/4"	12.8	4540-3W400	207	628.95
3CH0-05	5/16"	14.4	-	172	699.05
3CH0-06	3/8"	15.5	-	155	728.10
3CH0-08	1/2"	19.8	-	138	820.00

3DH0 SAE 100R7 Thermoplastic Hose

Meets or Exceeds:

- SAE 100R7

Applications:

- General hydraulics, mobile equipment, lift trucks and access platforms

Construction:

- Perforated black polyurethane cover
- Braided synthetic fibre reinforcement
- Polyester core tube
- Twin and multi lines available on request

Working Temperature:
-40°C to +100°C
(or to +66°C maximum with water based or fire resistant fluids)



Single Line, 75 Metre Continuous Coils

0235			Die Ref.		£
3DH0-03	3/16"	10	4540-30300	207	774.05
3DH0-04	1/4"	12.8	4540-30400	190	740.20
3DH0-05	5/16"	14.4	4540-30500	172	823.65
3DH0-06	3/8"	15.5	4540-30600	155	858.75
3DH0-08	1/2"	19.8	4540-A0800	138	963.90

30CT SAE 100R18 Thermoplastic Hose

Meets or Exceeds:

- SAE 100R18

Applications:

- General hydraulics, cold store applications, lift truck, mobile equipment, chemical and gas transfer

Construction:

- Black polyester cover
- Braided synthetic fibre reinforcement
- Composite polyester/polyurethane tube

Working Temperature:
-54°C to +94°C



Single Line, 75 Metre Continuous Coils

0235			Die Ref.		£
30CT-03	3/16	10.1	4540-303	207	391.90
30CT-04	1/4	12.14	4540-3W4	207	483.80
30CT-05	5/16	15.49	4540-305	207	477.70
30CT-06	3/8	16.76	4540-306	207	487.40
30CT-08	1/2	21.59	4540-A08	207	679.15

37BO Medium Pressure Hose

Meets or Exceeds:

- SAE100R7

Applications:

- General hydraulics, forklifts working in cold storage areas, mobile equipment, lift truck hydraulic systems and cold temperature motion control

Construction:

- Black polyester cover
- Braided synthetic fibre reinforcement
- Polyurethane core tube

Working Temperature:
-54°C to +100°C
(or to +60°C maximum with water based or fire resistant fluids)



Single Line, 75 Metre Continuous Coils

0235		Die Ref.		£
37BO-03	3/16"	4540-30300	207	727.40
37BO-04	1/4"	4540-30400	207	810.30
37BO-05	5/16"	4540-30500	172	924.60
37BO-06	3/8"	4540-30600	155	962.35

Port & Connector Identification Kit

Accurate identification of ports and connectors is made easy with this kit, allowing correct hose and tube assemblies to be selected and installed.

Metric & Imperial

0235

FT1341

£

157.15

