



Ball Valves

ISO 5211 Pad, WRAS Approved

- Full bore
- ISO 5211 direct mount

 Working Temperature:
-20°C to +95°C


 Maximum Working Pressure:
40 bar

Tech Sheet
10291

WRAS
APPROVED
PRODUCT




Female x Female, BSPP

	0090		£
LV4500-12	1/2"		45.90
LV4500-34	3/4"		59.10
LV4500-1	1"		78.80
LV4500-114	1.1/4"		131.70
LV4500-112	1.1/2"		177.25
LV4500-2	2"		262.55
LV4500-212	2.1/2"		1019.75


Direct Mount Ball Valves

Suitable for domestic water services, heating and air conditioning plants, and compressed air systems.

 Working Temperature:
-20°C to +130°C



Tech Sheet
68247



Female x Female, BSPP


	0109		£
BV1021-14	1/4"		83.30
BV1021-38	3/8"		83.30



Tech Sheet
68248




3 Way T Port Ball Valve, Female, BSPP

	0109		£
BV1070-14	1/4"		50.50
BV1070-38	3/8"		120.20
BV1070-12	1/2"		120.20
BV1070-34	3/4"		84.10
BV1070-1	1"		210.05
BV1070-114	1.1/4"		538.55
BV1070-112	1.1/2"		604.70
BV1070-2	2"		800.50



3 Way L Port Ball Valve, Female, BSPP

	0109		£
BV1071-14	1/4"		40.45
BV1071-38	3/8"		120.20
BV1071-12	1/2"		40.05
BV1071-34	3/4"		164.05
BV1071-1	1"		210.05
BV1071-114	1.1/4"		538.55
BV1071-112	1.1/2"		604.70
BV1071-2	2"		800.50

