Hydraulics

Hydraulic Quick Release Couplings Pneumatic Quick Release Couplings

& Test

Pneumatics

Pneumatic & Vacuum Equipment

Valves

Ring Main

Systems

Adaptors & Fittings

Stainless Steel

Malleable

Hose, Tubing & Couplings

Clamps & Clips

Sprays & Adhesives

Blow Guns, Vacuum & Nozzles Pressure Wash, Fuelling & Lubrication

Air Tools & Compressor Equipment

Thermoplastic Hose & Fittings

EAT•N Synflex

Working Temperature:

-40°C to +100°C (or to +66°C maximum with water

based or fire resistant fluids)

37AL Non-conductive Constant Pressure Hose

Meets or Exceeds:

SAE100R7 non-conductive

Applications:

· Electric utility truck hydraulic systems and mobile equipment (picker/utility vehicles)

Construction:

- · Orange non-perforated, non-stick polyurethane cover
- Braided synthetic fibre reinforcement
- Polyester core tube



Single Line, 76.2 Metre Non Continuous Coils

	<u> </u>				
0235	(ID-)	OD mm	Die Re f.	bar	£
37AL-03	3/16"	10.8	4540-303.00	207	1427.15
37AL-04	1/4"	12.3	4540-3W4	207	907.20
37AL-05	5/16"	14.7	4540-305	207	950.85
33AL-06	3/8"	16.1	4540-306	207	1231.20
37AL-08	1/2"	20.7	4540-308	207	1496.75

3E80 Non-conductive High **Pressure Hose**

Meets or Exceeds:

SAE100R8

Applications:

- · General hydraulic systems that may contact high voltage sources
- · Aerial equipment, mobile machinery and rescue tools

Construction:

- · Non-conductive marking and colour code
- Orange polyurethane non-perforated cover Braided synthetic fibre reinforcement
- · Nylon core tube



Single Line, 76.2 Metre Continuous Coils

0235	-ID-	Die Re f.	bar	£
3E80-04	1/4"	4540-H04	345	1266.70
3E80-06	3/8"	4540-H06	276	1583.30
3E80-08	1/2"	4540-H08	241	2115.20

3R80 High Pressure Hose

Meets or Exceeds:

SAE100R8

Working Temperature:

-54°C to +100°C (or to +60°C maximum

with water based or fire

resistant fluids

Applications:

- · General hydraulic systems
- · Hydraulic tools and mobile equipment
- · High pressure pneumatic systems and chemical transfer

Construction:

- · Black perforated polyurethane cover
- Braided synthetic fibre reinforcement
- Nylon core tube



Single Line, 76.2 Metre Continuous Coils

0235	-ID-	Die Re f.	bar	\mathfrak{Z}
3R80-03	3/16"	4540-H03	345	914.25
3R80-04	1/4"	4540-H04	345	1045.15
3R80-06	3/8"	4540-H06	276	1356.05
3R80-08	1/2″	4540-H08	241	1943.60

Single Line, 75 Metre Continuous Coils

0235	-ID-	Die Re f.	bar	\mathfrak{L}
3R80-16	1"	4540-H16	138	3967.95

Single Line, 61 Metre Non Continuous Coils





