

Butterfly Handles, Brass

- Full bore
- BS EN331
- Nickel plated
- Screwed BSPP Female x Female

Working Temperature:
Gas: -5°C to +60°C
Water/Oil: -5°C to +150°C

Maximum Working Pressure:
Gas: 5 bar
Water/Oil: 20 bar



Pro-Fit - Red, Female x Female, BSPP

0230		£
EPS-101600	1/4"	9.85
EPS-101605	3/8"	8.45
EPS-101610	1/2"	18.75
EPS-101615	3/4"	17.15
EPS-101620	1"	27.80

- Full bore
- BS EN331
- Nickel plated
- Screwed BSPP Male x Female

Working Temperature:
Gas: -5°C to +60°C
Water/Oil: -5°C to +150°C

Maximum Working Pressure:
Gas: 5 bar
Water/Oil: 20 bar



Pro-Fit - Red, Male x Female, BSPP

0230		£
EPS-101625	1/4"	13.85
EPS-101645	1"	27.80

- Full bore
- BS EN331
- Nickel plated
- Screwed BSPP Female x Female

Working Temperature:
Gas: -5°C to +60°C
Water/Oil: -5°C to +150°C

Maximum Working Pressure:
Gas: 5 bar
Water/Oil: 20 bar



Pro-Fit - Blue, Female x Female, BSPP

0230		£
EPS-101700	1/4"	9.85
EPS-101705	3/8"	5.40
EPS-101710	1/2"	18.75
EPS-101715	3/4"	15.90
EPS-101720	1"	27.80

- Full bore
- BS EN331
- Nickel plated
- Screwed BSPP Female x Female

Working Temperature:
Gas: -5°C to +60°C
Water/Oil: -5°C to +150°C

Maximum Working Pressure:
Gas: 5 bar
Water/Oil: 20 bar



Pro-Fit - Yellow, Female x Female, BSPP

0230		£
EPS-101455	1/4"	10.05
EPS-101460	3/8"	10.25
EPS-101465	1/2"	18.75
EPS-101470	3/4"	17.15
EPS-101475	1"	27.65

Standard Lever Ball Valves

Working Temperature:
Water/Oil: -5°C to +150°C

Maximum Working Pressure:
Water/Oil: 20 bar



Red Handle, BSPP

0109		£
BVNA-14	1/4"	9.55
BVNA-38	3/8"	12.75
BVNA-12	1/2"	10.75
BVNA-34	3/4"	14.30
BVNA-1	1"	25.15
BVNA-114	1.1/4"	34.30
BVNA-112	1.1/2"	51.40
BVNA-2	2"	84.10