

Plastic Ball Valves

Body:
Polypropylene with
Nitrile Seal



Maximum Working
Pressure:
3.5 bar



Hose Tail x Hose Tail

0270	To Suit Hose I.D. mm	£
18530-1	12	3.70
18530-2	16	3.70
18530-3	20	3.70



Male BSPP x Male BSPP

0270		£
18570-1	1/2"	3.00
18570-2	1/2" x 3/4"	3.00
18570-3	3/4"	3.00



Hose Tail x Female BSPP

0270	To Suit Hose I.D. mm		£
18563-1	16	1/2"	5.40
18563-2	16	3/4"	5.40
18563-3	20	1/2"	5.40
18563-4	20	3/4"	5.40



Hose Tail x Male BSPP

0270	To Suit Hose I.D. mm		£
18560-1	12	1/2"	3.80
18560-2	12	3/4"	3.80
18560-3	16	1/2"	3.80
18560-4	16	3/4"	3.80
18560-5	20	1/2"	3.80
18560-6	20	3/4"	3.80

Plastic Push-in Valves

Suitable for the use in the Food Industry.



Tech Sheet
10327



Tube x Tube

0270	OD mm	£
14330606	6	11.30
14331010	10	12.00
14331212	12	12.45



Tech Sheet
10326



BSPT Male x Tube

0270	OD mm		£
14340613	6	1/4"	11.20
14341017	10	3/8"	11.50
14341221	12	1/2"	12.25

Working
Temperature:
30°C to 85°C



Tech Sheet
10328



Maximum Working
Pressure:
11 bar



BSPP Female 90°

0270	OD mm		£
14350613	6	1/4"	12.70
14351017	10	3/8"	9.30
14351221	12	1/2"	13.75



In-line Mini Filter

0270	OD mm	£
14480606	6	16.55
14480808	8	17.35
14481010	10	18.15
14481212	12	19.10

Customers who bought from
this page also purchased...



Worm Drive Hose
Clamps



...see pages 1502-1503