



Safety Valves

Wade Safety Relief Valves - Series 6000

Specification: The Series 6000 is a high lift safety relief valve with atmospheric discharge suitable for air and inert gas applications. The flow is de-rated and measured in accordance with BS6759 Part 2: 1984. The valve re-seats by minus 10% of set pressure.



 **Working Temperature:**
-15°C to +140°C

 **Maximum Working Pressure:**
12.5 bar

Tech Sheet
10341





Series 6000 High Lift Safety Relief Valve, Male BSPT

0095			£
6000/06/G/5.5	1/4"	5.5	39.25
6000/06/H/9.0	1/4"	9	39.25
6000/06/J/11.0	1/4"	11	39.25

Tech Sheet
10341



Series 6200 High Lift Safety Relief Valve, Male BSPT



0095			£
6200/15/G/5.5	1/2"	5.5	87.20
6200/15/H/9.0	1/2"	9	96.95
6200/20/G/5.5	3/4"	5.5	104.55

Valves for higher pressure ratings are available. Safety valves are PED approved and CE marked.

Tech Sheet
10341



Series 6100 High Lift Safety Relief Valve, Male BSPT

0095			£
6100/06/J/11.0	1/4"	11	78.40
6100/10/J/11.0	3/8"	11	81.40
6100/15/G/5.5	1/2"	5.5	83.15
6100/15/H/9.0	1/2"	9	83.15
6100/15/J/11.0	1/2"	11	83.15
6100/20/J/11.0	3/4"	11	90.75
6100/25/J/11.0	1"	11	108.45


Wade

Pressure Relief Valves

All Series 1784 Valves are factory pre-set and sealed to prevent tampering. Manufactured under regulations of The National Board of Boiler & Pressure Vessel Inspectors in accordance with Section VIII of the ASME Code covering valves for pressure vessels.

Pre-set pressure relief valves are precision manufactured to protect against equipment damaged or personal injury that may result from dangerous pressure build-up.



- Automatically vents at selected pressure.
- Automatically resets when pressure returns to 'normal'.
- Brass body with stainless steel internal components.

 **Working Temperature:**
Type 1776:
0°C to +180°C
(0°F to +350°F)

Tech Sheet
835



Type 1776, Male, 1/4" NPT

0090			£
1776K-0-05	5	12	25.30
1776K-0-10	10	30	16.95
1776K-0-15	15	43	20.80
1776K-0-20	20	50	22.20
1776K-0-25	25	56	20.65
1776K-0-30	30	63	23.30
1776K-0-40	40	82	22.00
1776K-0-50	50	97	20.80
1776K-0-60	60	110	25.30
1776K-0-75	75	134	24.95

No Test Certs available on the above.

Individual Test Certs to be requested at the time of order on Wade Products

Valves for higher pressure ratings are available.
Safety valves are PED approved and CE marked.