

# Pressure Switches



## Direct Mount Pressure Switches

- Body: Brass
- Diaphragm: Silicone Rubber
- Damper Spring: Stainless Steel
- Microswitch: 10amp

Tech Sheet  
975



Brass, Suitable for Water, Steam & Aggressive Media, BSPT

0061			Fixed Differential bar	Repeatability bar	£
XP73AE61.000	1/8"	0.2-1.2	0.20±0.1	±0.15	32.70
XP73CE61.000	1/8"	1.0-2.5	0.20±0.1	±0.2	32.70
XP73DE61.000	1/8"	1.5-4.0	0.20±0.1	±0.2	32.70
XP73EE61.000	1/8"	2.0-6.0	0.30±0.1	±0.2	32.70

Tech Sheet  
10440

Brass, Suitable for Pumped Water Systems, Air & Low Pressure Hydraulics, BSPT

0061			Fixed Differential bar	Repeatability bar	£
GP73ME31.000	1/8"	0.2-3.0	0.25±0.1	±0.2	25.65
GP73PE31.000	1/8"	1.0-5.0	0.25±0.1	±0.2	29.85

- Ideal for hot water, steam & semi-aggressive media.

Ambient Temperature: -10°C to +50°C  
Working Temperature: -10°C to +125°C

Tech Sheet  
976

Stainless Steel, Suitable for Hot Water, Steam & Semi-aggressive Media, BSPT

0030			£
XP83FE61000	1/8"	4.0-9.0	62.75
XP83GE61000	1/8"	9.0-15.0	62.75

## Strainer for Condensate Drain

- Strainer consisting of a ball valve with filter to be used together with an automatic drain valve. In order to clean & check the filter it is sufficient to close the valve to isolate it & then unscrew the plug.

Ambient Temperature: -10°C to +50°C  
Working Temperature: -10°C to +130°C

Tech Sheet  
978



BSPP

0030			£
887057000	1/2"	1/2"	26.80
887058000	3/8"	1/2"	24.95
887059000	1/4"	1/2"	24.95

For...



Galvanised Fittings



...see pages 1252-1261

- Hydraulics
- Hydraulic Quick Release Couplings
- Pneumatic Quick Release Couplings
- Air Prep, Media, Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns, Vacuum & Nozzles
- Pressure Wash, Fuelling & Lubrication
- Air Tools & Compressor Equipment
- Tools, Hardware & PPE