

# Butterfly Wafer Pattern Valves

## Cast Iron Body, Stainless Steel Disc, EPDM Liner

Suitable for Flanges:  
BS 10 Table D/E, PN6/10/16 & ANSI150

Working Temperature:  
-20°C to +120°C



Tech Sheet  
14

### Lever Operated

0030	Flange Size	£
LEVER/40SSEP	1.1/2"	74.50
LEVER/50SSEP	2"	75.80
LEVER/65SSEP	2.1/2"	78.45
LEVER/80SSEP	3"	89.55
LEVER/100SSEP	4"	119.60
LEVER/125SSEP	5"	180.15
LEVER/150SSEP	6"	215.90
LEVER/200SSEP	8"	347.15
LEVER/250SSEP	10"	581.05

Suitable for Flanges:  
BS 10 Table D/E, PN6/10/16 & ANSI150

Working Temperature:  
-20°C to +120°C



Tech Sheet  
14

### Gear Operated

0030	Flange Size	£
GEAR/50SSEP	2"	148.60
GEAR/65SSEP	2.1/2"	163.35
GEAR/80SSEP	3"	173.30
GEAR/100SSEP	4"	210.65
GEAR/125SSEP	5"	261.00
GEAR/150SSEP	6"	326.20
GEAR/200SSEP	8"	546.05
GEAR/250SSEP	10"	812.15
GEAR/300SSEP	12"	1153.50
GEAR/350SSEP	14"	1523.40
GEAR/400SSEP	16"	2718.95

Suitable for Flanges:  
BS 10 Table D/E, PN6/10/16 & ANSI150

Working Temperature:  
-20°C to +120°C



Tech Sheet  
15

### Pneumatic Single Acting

0030	Flange Size	£
SA/50SSEP	2"	578.30
SA/65SSEP	2.1/2"	642.95
SA/80SSEP	3"	781.05
SA/100SSEP	4"	890.40
SA/125SSEP	5"	1273.15
SA/150SSEP	6"	1818.85
SA/200SSEP	8"	3604.85
SA/250SSEP	10"	3751.40
SA/300SSEP	12"	7013.40

Suitable for Flanges:  
BS 10 Table D/E, PN6/10/16 & ANSI150

Working Temperature:  
-20°C to +120°C

Tech Sheet  
16

### Pneumatic Double Acting

0030	Flange Size	£
DA/50SSEP	2"	289.80
DA/65SSEP	2.1/2"	367.45
DA/80SSEP	3"	375.10
DA/100SSEP	4"	445.35
DA/125SSEP	5"	559.95
DA/150SSEP	6"	628.70
DA/200SSEP	8"	910.65
DA/250SSEP	10"	1297.15
DA/300SSEP	12"	2663.00

Suitable for Flanges:  
PN16 (ANSI150 on request).

- Electric Actuator Safe Area 85 - 240V AC or DC single Phase (10" and 12" 230V AC Only).
- Battery Backup Failsafe and Modulating (4-20mA or 0-10V) on request.
- ATEX Approved Actuator on request.



Working Temperature:  
-20°C to +100°C

Tech Sheet  
17

### Electric Actuated, Multi Voltage

0030	Flange Size	£
E/40SSEP-MV	1.1/2"	608.85
E/50SSEP-MV	2"	608.85
E/65SSEP-MV	2.1/2"	704.50
E/80SSEP-MV	3"	904.90
E/100SSEP-MV	4"	1194.05
E/125SSEP-MV	5"	1702.65

Working Temperature:  
-20°C to +120°C

Tech Sheet  
17

### Electric Actuated, High Voltage

0030	Flange Size	£
E/150SSEP-HV	6"	1714.15
E/200SSEP-HV	8"	1982.80

Suitable for Flanges:  
BS 10 Table D/E, PN6/10/16 & ANSI150

Working Temperature:  
-20°C to +120°C

Tech Sheet  
17

### Electric Actuated, Low Voltage

0030	Flange Size	£
E/150SSEP-LV	6"	1714.15
E/200SSEP-LV	8"	1982.80

For...



Galvanised Tubing



...see page 1262