

Butterfly Wafer Pattern Valves

Cast Iron Body, Stainless Steel Disc, Silicon Liner

Suitable for Flanges:
BS10 Table E, PN10/16, ANSI150.

Working Temperature:
-40°C to +200°C



Tech Sheet
14

Lever Operated

0030	Flange Size	£
LEVER/50SSSIL	2"	546.90
LEVER/65SSSIL	2.1/2"	599.35
LEVER/80SSSIL	3"	759.35
LEVER/100SSSIL	4"	1247.40
LEVER/125SSSIL	5"	1710.90
LEVER/150SSSIL	6"	1827.85
LEVER/200SSSIL	8"	2245.50
LEVER/250SSSIL	10"	4047.35

Suitable for Flanges:
BS10 Table E, PN10/16, ANSI150.

Working Temperature:
-40°C to +200°C



Tech Sheet
14

Gear Operated

0030	Flange Size	£
GEAR/50SSSIL	2"	546.90
GEAR/65SSSIL	2.1/2"	599.35
GEAR/80SSSIL	3"	759.35
GEAR/100SSSIL	4"	1247.40
GEAR/125SSSIL	5"	1710.90
GEAR/150SSSIL	6"	1827.85
GEAR/200SSSIL	8"	2245.50
GEAR/250SSSIL	10"	4047.35
GEAR/300SSSIL	12"	4776.25

Suitable for Flanges:
BS10 Table E, PN10/16, ANSI150.

Working Temperature:
-40°C to +200°C



Tech Sheet
15

Pneumatic Single Acting

0030	Flange Size	£
SA/50SSSIL	2"	546.90
SA/65SSSIL	2.1/2"	599.35
SA/80SSSIL	3"	759.35
SA/100SSSIL	4"	1247.40
SA/125SSSIL	5"	1710.90
SA/150SSSIL	6"	1827.85
SA/200SSSIL	8"	2245.50
SA/250SSSIL	10"	4047.35
SA/300SSSIL	12"	4776.25

Suitable for Flanges:
BS10 Table E, PN10/16, ANSI150

Actuator:
Rilsan Coated Aluminium Body,
1/4" BSP Female Ports.
• Actuator assembly based on 6 bar Pilot Air.

Working Temperature:
-40°C to +200°C

Tech Sheet
16

Pneumatic Double Acting

0030	Flange Size	£
DA/50SSSIL	2"	437.40
DA/65SSSIL	2.1/2"	541.50
DA/80SSSIL	3"	604.20
DA/100SSSIL	4"	754.05
DA/125SSSIL	5"	994.80
DA/150SSSIL	6"	1178.25
DA/200SSSIL	8"	1737.15
DA/250SSSIL	10"	2569.90
DA/300SSSIL	12"	4050.60

Suitable for Flanges:
PN10/16, ANSI150 & BS10 Table E.

- Electric Actuator Safe Area 85 - 240V AC or DC single Phase (10" and 12" 230V AC Only).
- Battery Backup Failsafe and Modulating (4-20mA or 0-10V) on request.
- ATEX Approved Actuator on request.

Working Temperature:
-60°C to +190°C



Electric Actuated, Multi Voltage

0030	Flange Size	£
E/50SSSIL-MV	2"	725.40
E/65SSSIL-MV	2.1/2"	878.60
E/80SSSIL-MV	3"	1134.05
E/100SSSIL-MV	4"	1502.75
E/125SSSIL-MV	5"	2137.55

Working Temperature:
-40°C to +200°C

Tech Sheet
17

Electric Actuated, High Voltage

0030	Flange Size	£
E/150SSSIL-HV	6"	2263.60
E/200SSSIL-HV	8"	2809.30

Suitable for Flanges:
BS10 Table E, PN10/16, ANSI150.

Working Temperature:
-40°C to +200°C

Tech Sheet
17

Electric Actuated, Low Voltage

0030	Flange Size	£
E/150SSSIL-LV	6"	1827.85
E/200SSSIL-LV	8"	2245.50

For...

CONAH

Plastic Hose Reels



...see page 1419

Products highlighted in yellow are new