

Butterfly Lugged Pattern PN16 Valves

HUK valves


7. Valves

- Hydraulics
- Hydraulic Quick Release Couplings
- Pneumatic Quick Release Couplings
- Air Prep, Media, Monitor & Test
- KELM™ Pneumatics
- Pneumatic & Vacuum Equipment
- Valves
- Ring Main Systems
- Adaptors & Fittings
- Stainless Steel
- Malleable Iron
- Hose, Tubing & Couplings
- Clamps & Clips
- Sprays & Adhesives
- Blow Guns, Vacuum & Nozzles
- Pressure Wash, Fuelling & Lubrication
- Air Tools & Compressor Equipment
- Tools, Hardware & PPE

Cast Iron Body, Stainless Steel Disc, NBR Liner

Suitable for Flanges:
PN16 (PN10, BS10 Table E and ANSI150 on request)

- Cast Iron Body, Stainless Steel Disc, NBR Liner
- Gear box on request.

 Working Temperature:
-12°C to +80°C




Tech Sheet 14

Lever Operated

0030	Flange Size	£
L/LEVER/40SSNBR	1.1/2"	90.80
L/LEVER/50SSNBR	2"	91.55
L/LEVER/65SSNBR	2.1/2"	108.00
L/LEVER/80SSNBR	3"	122.60
L/LEVER/100SSNBR	4"	169.70
L/LEVER/125SSNBR	5"	225.75
L/LEVER/150SSNBR	6"	262.25
L/LEVER/200SSNBR	8"	470.10
L/LEVER/250SSNBR	10"	774.20

Suitable for Flanges:
PN16 (PN10, BS10 Table E and ANSI150 on request)

- Actuator:
Rilsan Coated Aluminium Body,
1/4" BSP Female Ports.
- Actuator assembly based on 6 bar Pilot Air

 Working Temperature:
-12°C to +80°C




Tech Sheet 15

Pneumatic Single Acting

0030	Flange Size	£
L/SA/50SSNBR	2"	462.60
L/SA/65SSNBR	2.1/2"	525.85
L/SA/80SSNBR	3"	630.95
L/SA/100SSNBR	4"	750.95
L/SA/125SSNBR	5"	1061.30
L/SA/150SSNBR	6"	1489.35
L/SA/200SSNBR	8"	2932.35
L/SA/250SSNBR	10"	3236.45
L/SA/300SSNBR	12"	5773.80

Suitable for Flanges:
PN16 (ANSI150 on request).

- Actuator:
Rilsan Coated Aluminium Body,
1/4" BSP Female Ports.
- Actuator assembly based on 6 bar Pilot Air.

 Working Temperature:
-12°C to +80°C


Tech Sheet 16

Pneumatic Double Acting

0030	Flange Size	£
L/DA/50SSNBR	2"	331.60
L/DA/65SSNBR	2.1/2"	414.70
L/DA/80SSNBR	3"	429.20
L/DA/100SSNBR	4"	508.20
L/DA/125SSNBR	5"	638.25
L/DA/150SSNBR	6"	732.15
L/DA/200SSNBR	8"	1145.70
L/DA/250SSNBR	10"	1717.85
L/DA/300SSNBR	12"	3362.50

Suitable for Flanges:
PN16 (PN10, BS10 Table E and ANSI150 on request)


- Electric Actuator Safe Area 85 - 240V AC or DC single Phase (10" and 12" 230V AC Only).
- Battery Backup Failsafe and Modulating (4-20mA or 0-10V) on request
- ATEX Approved Actuator on request

 Working Temperature:
-0°C to +80°C



Electric Actuated, Multi Voltage

0030	Flange Size	£
L/E/40SSNBR-MV	1.1/2"	619.50
L/E/50SSNBR-MV	2"	619.50
L/E/65SSNBR-MV	2.1/2"	751.70
L/E/80SSNBR-MV	3"	959.15
L/E/100SSNBR-MV	4"	1257.00
L/E/125SSNBR-MV	5"	1780.65

 Working Temperature:
-12°C to +80°C


Tech Sheet 17

Electric Actuated, High Voltage

0030	Flange Size	£
L/E/150SSNBR-HV	6"	1817.20
L/E/200SSNBR-HV	8"	2217.90

Suitable for Flanges:
PN16 (ANSI150 on request).

- Electric Actuator Safe Area 12-24V AC or DC single Phase (10" and 12" 24V AC/DC Only).
- Battery Backup Failsafe and Modulating (4-20mA or 0-10V) on request.
- ATEX Approved Actuator on request.

 Working Temperature:
-12°C to +80°C

Tech Sheet 17

Electric Actuated, Low Voltage

0030	Flange Size	£
L/E/150SSNBR-LV	6"	1817.20
L/E/200SSNBR-LV	8"	2217.90

For...


german engineering at your service

1620 Test Point
Kits



...on page 195

Products highlighted in yellow are new

HYDRAQUIP
HOSE & HYDRAULICS
www.hydraquip.co.uk