

SANHA[®]

NiroSan[®] Copper Press Piping System



NiroSan[®] Series 6000 copper press fittings for copper pipes, according to EN1057, suitable for drinking water and heating installations. SANHA press system fittings are well known for outstanding quality. They are easy to work with and offer the right solution for a wide range of applications, be they residential or office buildings. They come with black moulded sealing rings. The fittings are ideal for combining with our unique PURAPRESS Series 8000, made of completely lead-free copper alloy silicon bronze. All SANHA Series 6000 system press fittings are tested and certified by all relevant national and international certification bodies.

Features

- Pressable with V, M and SA profiles
- Suitable for a very broad range of applications
- Long service life of fittings and EPDM sealing rings
- Inseparable, pressure-formed connection
- WRAS tested and certified
- All fittings are manufactured from high quality copper and are suitable to connect to copper pipes, all as EN1057



Working Temperature:
-30°C to +120°C


Tech Sheet
68233



Maximum Working Pressures:

Water: 16 bar
Flammable Gases: 5 bar
Non-flammable/Toxic Gases: 16 bar

Series 6000, Straights



Female x Male Plain End, Reducer

0473	ID mm	OD mm	£
162432215	22	15	3.15
162432815	28	15	8.65
162432822	28	22	8.90
162433522	35	22	10.75
162433528	35	28	11.85
162434222	42	22	18.45
162434228	42	28	17.60
162434235	42	35	17.60
162435435	54	35	23.80
162435442	54	42	23.80
162436728	67	28	69.20
162436735	67	35	69.20
162436742	67	42	69.20
162436754	67	54	83.75

Slip Coupling



0473	ID mm	£
16270515	15	5.80
16270522	22	9.05
16270528	28	13.40
16270535	35	17.15
16270542	42	24.60
16270554	54	31.30
16270567	67	91.40

Series 6000, End Caps



Female

0473	ID mm	£
1630115	15	6.05
1630122	22	7.05
1630128	28	11.15
1630135	35	19.20
1630142	42	28.80
1630154	54	34.65
1630167	67	66.15

Coupling



0473	ID mm	£
1627015	15	2.75
1627022	22	4.25
1627028	28	9.05
1627035	35	11.35
1627042	42	20.50
1627054	54	26.10
1627067	67	63.00

Reducing Coupling



0473	ID mm	ID mm	£
162402215	22	15	12.30
162402815	28	15	17.80
162402822	28	22	18.70
162403522	35	22	20.50
162403528	35	28	39.75
162404222	42	22	59.40
162404228	42	28	32.15
162404235	42	35	71.65
162405428	54	28	45.50
162405435	54	35	46.25
162405442	54	42	91.35