

# 3000lb Pipe Fittings, ANSI B16.11

Page Tech Sheet 68007

Working Temperature:  
0°C to +180°C



Maximum Working Pressure:  
206 bar

Pressure and temperature ratings  
according to ASME B16.11

Available up to 4"

## 90° Equal Elbow



Female Thread, NPT

0506		£
1013-0001	1/4"	5.45
1013-0002	3/8"	5.45
1013-0003	1/2"	5.45
1013-0004	3/4"	7.15
1013-0005	1"	11.40
1013-0006	1.1/4"	17.60
1013-0007	1.1/2"	23.25
1013-0008	2"	30.60

## Equal Hexagon Nipple



Male Thread, NPT

0506		£
1013-0025	1/4"	4.70
1013-0026	3/8"	4.70
1013-0027	1/2"	4.70
1013-0028	3/4"	5.70
1013-0029	1"	8.10
1013-0030	1.1/4"	12.10
1013-0031	1.1/2"	13.70
1013-0032	2"	17.15

## Hexagon Plug



Male Thread, NPT

0506		£
1013-0041	1/4"	2.15
1013-0042	3/8"	2.15
1013-0043	1/2"	2.15
1013-0044	3/4"	2.60
1013-0045	1"	4.25
1013-0046	1.1/4"	6.50
1013-0047	1.1/2"	8.45
1013-0048	2"	10.80

## Equal Tee



Female Thread, NPT

0506		£
1013-0009	1/4"	6.85
1013-0010	3/8"	6.85
1013-0011	1/2"	6.85
1013-0012	3/4"	10.10
1013-0013	1"	14.85
1013-0014	1.1/4"	21.85
1013-0015	1.1/2"	30.50
1013-0016	2"	40.30

## Equal Union



Female Thread, NPT

0506		£
1013-0033	1/4"	9.20
1013-0034	3/8"	9.20
1013-0035	1/2"	9.20
1013-0036	3/4"	11.05
1013-0037	1"	14.00
1013-0038	1.1/4"	24.40
1013-0039	1.1/2"	27.65
1013-0040	2"	35.30

## Equal Coupling



Female Thread, NPT

0506		£
1013-0049	1/4"	2.70
1013-0050	3/8"	2.70
1013-0051	1/2"	2.70
1013-0052	3/4"	3.75
1013-0053	1"	5.20
1013-0054	1.1/4"	9.35
1013-0055	1.1/2"	10.90
1013-0056	2"	14.40

## Round Cap



Female Thread, NPT

0506		£
1013-0017	1/4"	2.25
1013-0018	3/8"	2.25
1013-0019	1/2"	2.25
1013-0020	3/4"	3.15
1013-0021	1"	4.35
1013-0022	1.1/4"	6.35
1013-0023	1.1/2"	7.50
1013-0024	2"	9.40