

CLAMP 216



Sealing Clamp for watertight attachment of heavy, externally corrugated spiral hoses

Properties

- leak-proof and firmly clamping with special spiral geometry
- easily and quickly fitted
- re-usable (threaded)
- rust-proof
- very robust
- conform to RoHS guideline

Design, Material

1. Clamp strip: W2 stainless steel 1.4016 = AISI 430; Clamp wire: stainless steel 1.4310 / AISI 301 / W2 (INOX)
2. screw: chromated steel; Body: W2 stainless steel 1.4016

Delivery variants

- further diameters available on request.

Suitable for hose

AIRDUC®: 355+356, INOX 355+356 MHF-AS, 355+356 EC, 355+356 MHF, INOX 355+356 MHF, 355 Extra
 AIRDUC®: HT-PUR 355+356
 TIMBERDUC®: 534 SE

Suitable for Hose I.D. mm	Order No.
Sealing clamp for AIRDUC® 345, 355, 534 hoses with an inner Ø of <50 mm	
32	216-0032-2872
38	216-0038-2872
40	216-0040-2872
45	216-0045-2872
Sealing clamp for AIRDUC® 356 hoses with an inner Ø of <50 mm	
32	216-0032-2010
38	216-0038-2010
40	216-0040-2010
45	216-0045-2010
Sealing clamp for AIRDUC® 345, 355, 534, 356 hoses with an inner Ø of ≥50 mm	
50	216-0050-0000
55	216-0055-0000
60	216-0060-0000
65	216-0065-0000
70	216-0070-0000
75	216-0075-0000
80	216-0080-0000
90	216-0090-0000
100	216-0100-0000
102	216-0102-0000
110	216-0110-0000
115	216-0115-0000
120	216-0120-0000
125	216-0125-0000
127	216-0127-0000
130	216-0130-0000
140	216-0140-0000
150	216-0150-0000

	Suitable for Hose I.D. mm	Order No.
	152	216-0152-0000
	160	216-0160-0000
	175	216-0175-0000
	180	216-0180-0000
	200	216-0200-0000
	225	216-0225-0000
	250	216-0250-0000
	275	216-0275-0000
	300	216-0300-0000

Further diameters available on request. All values indicated here are approximate figures based on a temperature of 20°C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.

Accessories



CONNECT 270-271