


CONNECT 270-271



Metal hose connector / reducer

Properties

- easily and quickly fitted
- re-usable
- rust protected
- conform to RoHS guideline

Temperature Range

- 200°C

Design, Material

galvanised sheet metal

Delivery variants

- further diameters available on request.
- Stainless Steel (INOX)

Suitable for hose

PROTAPE®: 301, 370, 327 MEMORY; MHF: 330+331, 335 FLAT, CU 335 FLAT, INOX 330, INOX-AS 330; PVC: 310+371; TPE: 320+326 MEMORY; PE: 322 EC
AIRDUC®: 353+355, 350-355 MHF, 351+355 HT-PUR + EC + ExTra + INOX MHF + INOX MHF-AS; 355 CSH + REINFORCED + ORANGE; PVC:

341+345; TPE: 363; PE: 362 EC + F
TIMBERDUC®: 531-534, 532 CNC
CP: Aramid: 461+461 PROTECT; HiTex: 480-487 + 467 WELDING; HYP: 450+450 PROTECT; PE: 457+457 EC; PTFE: GLASS-INOX, 471+471 EC + HYP-INOX 472+472 EC + INOX 475 EC+F; 455 MHF; PVC: 465+465 HT; 460 SIL; 459 EC; Kapton® 476
NORPLAST®: 385, CU 386; PVC: 379+380 Superelastic, 380 GREEN, 383; 384; CU 384
NEO: 1+2
SIL: 1+2
SuperFlex PVC 372

Suitable for Hose I.D. d1	Suitable for Hose I.D. d2	Adapter length I1	Adapter length I2	Total Length I3	Wall Thickness mm	Weight kg/Pcs	Order No.
Hose connector							
50	50	40	40	90	0,6	0,200	270-0050-0000
60	60	40	40	90	0,6	0,200	270-0060-0000
70	70	40	40	90	0,6	0,200	270-0070-0000
75	75	40	40	90	0,6	0,200	270-0075-0000
80	80	40	40	90	0,6	0,200	270-0080-0000
90	90	40	40	90	0,6	0,200	270-0090-0000
100	100	40	40	90	0,6	0,200	270-0100-0000
110	110	40	40	90	0,6	0,300	270-0110-0000
120	120	40	40	90	0,6	0,300	270-0120-0000
125	125	40	40	90	0,6	0,300	270-0125-0000
130	130	40	40	90	0,6	0,300	270-0130-0000
140	140	40	40	90	0,6	0,400	270-0140-0000
150	150	40	40	90	0,6	0,500	270-0150-0000
160	160	40	40	90	0,6	0,500	270-0160-0000
170	170	40	40	90	0,6	0,500	270-0170-0000
175	175	40	40	90	0,6	0,600	270-0175-0000
180	180	40	40	90	0,6	0,600	270-0180-0000
200	200	40	40	90	0,6	0,600	270-0200-0000
215	215	40	40	90	0,6	0,700	270-0215-0000
225	225	40	40	90	0,6	0,700	270-0225-0000
250	250	60	60	130	0,6	0,800	270-0250-0000
275	275	60	60	130	0,6	0,900	270-0275-0000
300	300	60	60	130	0,7	1,000	270-0300-0000
315	315	60	60	130	0,7	1,100	270-0315-0000
325	325	60	60	130	0,7	1,200	270-0325-0000
350	350	60	60	130	0,7	1,300	270-0350-0000
375	375	80	80	170	0,7	1,500	270-0375-0000
400	400	80	80	170	0,7	1,600	270-0400-0000

Suitable for Hose I.D. d1	Suitable for Hose I.D. d2	Adapter length l1	Adapter length l2	Total Length l3	Wall Thickness mm	Weight kg/Pcs	Order No.
450	450	80	80	170	0,7	2,100	270-0450-0000
500	500	80	80	170	0,7	2,300	270-0500-0000

Hose reduction							
75	50	40	40	135	0,6	0,200	271-0075-0000
80	70	40	40	125	0,6	0,200	271-0080-0000
100	80	40	40	140	0,6	0,200	271-0100-0000
125	100	40	40	145	0,6	0,300	271-0125-0000
150	100	40	40	175	0,6	0,300	271-0150-0000
200	150	40	40	175	0,6	0,500	271-0200-0000
250	200	60	40	200	0,6	0,800	271-0250-0000
300	200	60	40	265	0,7	1,200	271-0300-0000
80	50	40	40	135	0,6	0,200	271-0080-2655
100	70	40	40	150	0,6	0,200	271-0100-2660
125	80	40	40	175	0,6	0,300	271-0125-2665
150	80	40	40	205	0,6	0,400	271-0150-2670
150	125	40	40	145	0,6	0,300	271-0150-2671
200	100	40	40	245	0,6	0,600	271-0200-2675
200	125	40	40	215	0,6	0,600	271-0200-2676
250	125	60	40	300	0,6	1,000	271-0250-2680
250	150	60	40	270	0,6	0,900	271-0250-2681
300	150	60	40	335	0,7	1,300	271-0300-2685
300	250	60	40	195	0,7	1,300	271-0300-2687

Further diameters available on request. All values indicated here are approximate figures based on a temperature of 20°C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.

Accessories



CLAMP 212



CLAMP 216



CLAMP 208



CLAMP 211



CLAMP 212 EC



CLAMP 217



CLAMP 213



CONNECT 223