

Liquid Level Gauges



EasyFit Gauges

EasyFit liquid level gauges are available up to 1 metre.

Suitable for many industrial & domestic usages, subject to pressure & material compatibility.

Lower Body: Brass.

Fixing Bolts: Brass.

Seals: FKM.

Sight Tube: Polycarbonate.


Guard Tube: Polycarbonate.

Adaptor: Brass.

Tank Seals:

Dowty sealing washer.

 **Maximum Temperature:**
+60°C

 **Maximum Pressure:**
14 bar
(subject to centre distance selected)



Easy fit liquid level gauge

The Easy-fit Liquid level gauge, has top and bottom valveless connections the banjo fittings are Brass Natural finish, and the base size is G1/4" BSP-P. the gauge is supplied with two adaptors which will allow you to increase the size of the connection to either G3/8" BSP-P or G1/2" BSP-P. The sight tube has a Polycarbonate outer guard tube, the sight tube is only available in Polycarbonate Plastic complete with Red line to assist in the level reading. Maximum centre distance is 1000 mm, this gauge has an maximum operating pressure of 14 Bar depending on the length- Not recommended above 65°C

Connection: G1/4" - G1/2" BSP Male

Maximum pressure: 14 Barg (subject to centre distance selected.)

Maximum temperatures: +65°C

Length (mm): 100 - 1000 (Can be manufactured to special lengths.

Contact our technical sales department for details)

Lower body, fixing bolt material: Natural Brass

Seal material: FKM

Sight & guard tube material: Polycarbonate Plastic

Adaptor material: Brass