


Belt Dressing FG

Food Processing Safe PTFE Lubricant



Technical Data

A clear liquid formulated specially for use on all types of belts found in food manufacturing equipment to increase pulling power, prevent belt slippage due to heat, cold, dampness or dust, and eliminate belt squeak, where incidental food contact may occur.

FEATURES

- NSF H1 registered (N° 140257) and has been formulated for use in the food industry.
- Works on all type of belt - vee, flat, toothed, rubber, leather, and fabric
- Keeps belts 'soft' and glaze free
- Protects belts from deterioration through oxidation and heat
- Waterproof

APPLICATIONS

Eliminates slippage in flat, round or V-belts made out of rubber, leather, fabrics, plastic etc, used on:

- Compressors
- Pumps
- Generators
- Fans
- Motors
- Lift trucks
- Conveyors
- Industrial machinery

DIRECTIONS

- Turn off equipment and stop belts before applying
- Spray a light, even coating on pulling sides of belt (i.e. sides that come in contact with pulleys); let solvent evaporate before re-energising equipment
- Re-apply occasionally to ensure continued high performance
- Remove, if necessary, with Amberklene FG or Industrial Degreaser FG (test compatibility with rubber and plastic prior to use)


TECHNICAL DATA

NSF Registered, Category	:	H1 (N° 140257)
Appearance	:	Clear Liquid
Specific Gravity (@ 20°C)	:	0.75
Flash Point (closed cup)	:	< 0°C
Specific Gravity (@ 20°C)	:	0.91
Max. temp. (continuous)	:	100°C
Viscosity (@ 99°C)	:	4100 mPa.s
Average mol. Wt	:	2300
Packaging	:	400ml Aerosol



PART NUMBER:
6150009480





Based upon the present state of our knowledge and information received from our suppliers, evaluation of this product indicates that it is free from nut oils and their derivatives

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.