

Pressure Sprayers



Technical data

Type of device	Max. filling quantity	Total contents	Max. pressure	Max. temperature	Weight when empty	Material of tank	Max. pumping volume
3132...	1.0 l	1.15 l	3 bar	30 °C	365 g	Polyethylene	1.15 l / 3 bar
3132...	1.5 l	1.60 l	3 bar	30 °C	410 g	Polyethylene	1.15 l / 3 bar

Welcome and congratulations

for purchasing your new **pressure sprayer**. Thank you for the trust you have shown in our brand.

Intended Use

Pressure sprayers 3132... 1.0 l and 1.5 l are designed for spraying detergents, disinfectants, anti-corrosion agents, impregnating agents and other care products.

Not suitable for, and not to be used under any circumstances for:

- highly flammable and flammable liquids
- solvents and liquids containing solvents
- highly viscous or sticky liquids or liquids that leave residue which cannot be completely rinsed out of the device.

Products other than those approved by the manufacturer as well as usage for purposes excluded above are not in conformity with proper use.

The manufacturer shall not be liable for any resulting damages or for unauthorized modifications to the device.

Your Safety

Do not leave the device in the sun.

Check each time before using:

- Are all parts that are under pressure and convey liquids free of damage?
- Are those parts functioning properly?

Replace devices that are damaged or not functioning properly immediately.

Follow the spray manufacturer's instructions.

Do not leave under pressure for an extended period of time.

Never direct spray at persons, animals, or bodies of water.

Do not unscrew the pump from the tank when device is under pressure.

Do not blow through clogged nozzles or valves with your mouth.

Making the Device Ready for Use

- Turn the pressure release valve on the side until the pressure is released from the tank.
- Unscrew the pump from the tank.
- Add spraying liquid to the tank up to the filling line.
- Screw the pump tightly onto the tank.
- Generate pressure in the tank by activating the pump (max 15 pump strokes).

Use

- To spray, activate the lever on the pump.
- Releasing the lever interrupts the spray process immediately.
- The spray pattern can be optimally adjusted by turning the nozzle.

After Usage

- Turn the pressure release valve on the side until the pressure is released from the tank.
 - Unscrew the pump from the tank.
 - Do not dispose of residue as wastewater through the drain!
- Dispose of surplus environmentally harmful products as hazardous waste.