



2 Way Valves

2/2 Valves for all fluids and air Magnalift

BRASS		PIPE MOUNTING			NORMALLY CLOSED															
Port size	Orifice Ø	Flow factors			Seat Seal	Atex Zone	Operating Pressure Differential		Fluid Temp.		Power	Voltage	Solenoid Valve Order Number							
		Kv l/min	KV m³/h	Qn l/min			Min bar	Max bar	Min °C	Max °C				W						
3/8"	15	65	3.90	4500	NBR	-	0	16	-10	100	8	220-230V/50Hz	221G13-2995-4818653D							
							0	6	-10	100	14	24 Vdc	221G13-2995-492425C2							
						2-22	0	16	-10	65	8	220-230V/50Hz	221G13-2995-4958703D							
						1-21	0	16	-10	80	8	230V/50Hz	221G13-495905F4							
						1/2"	15	65	3.90	4500	FKM	-	0	16	-10	100	8	220-230V/50Hz	221G15-2995-4818653D	
													0	6	-10	100	14	24 Vdc	221G15-2995-492425C2	
2-22	0	16	-10	65								8	220-230V/50Hz	221G15-2995-4958703D						
1-21	0	16	-10	80								8	230V/50Hz	221G15-495905F4						
1/2"	15	65	3.90	4500								FKM	-	0	10	-10	100	9	24 Vdc	221G1530-2995-481865C2
														0	10	-10	65	9	24 Vdc	221G1530-2995-495870C2
						1-21	0	10	-10	80			8	24 Vdc	221G1530-495905C2					
						1/2"	15	65	3.90	4500			FKM	-	0	16	0	100	8	220-230V/50Hz
					0										5	0	100	14	24 Vdc	221G25-2995-492425C2
					2-22									0	16	0	65	8	220-230V/50Hz	221G25-2995-4958703D
1-21	0	16	0	80	8									230V/50Hz	221G25-495905F4					
1/2"	15	65	3.90	4500	FKM									-	0	10	-10	100	9	24 Vdc
											0				10	-10	65	9	24 Vdc	221G2530-2995-495870C2
						1-21	0	10	-10	80	8			24 Vdc	221G2530-495905C2					

