

# LOCTITE®

## 7840 Cleaner & Degreaser



### Product Description

LOCTITE® 7840™ provides the following product characteristics:

Technology	Solvent-based
Chemical type	Water, proprietary solvents, surfactants and conditioners
Appearance	Blue liquid
Viscosity	Very low
Cure	Not applicable
Application	Surface preparation
Specific benefit	Non-flammable, non-caustic

LOCTITE® 7840™ is a concentrated, biodegradable cleaner/degreaser that contains no hazardous solvents and dilutes with water to meet a wide range of industrial cleaning applications. Typical applications for this product include engines, motors, castings, valves, bearings, tanks, machinery, exterior siding, windows, carpets, concrete floors, asphalt, vehicles, etc. Substances it can remove include grease, lubricants, cutting oils, fuel oils, tar, road salt, light carbon, food stains, wax, animal fat, mildew, and soot. This product has a pine odour but is also available fragrance-free.

### Typical Properties

Specific gravity @ 25°C	1.02
Flash point – see SDS	

### General Information

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Safety Data Sheet (SDS).

### Directions for Use:

- 1 Dilute LOCTITE® 7840™ with warm or cold water.
- 2 Soak or spray parts with LOCTITE® 7840™ and wipe or rinse clean.
- 3 Dilution levels will vary depending upon the type and amount of substance being removed and the type of surface being cleaned. It is best to begin with a high concentration of LOCTITE® 7840™ and progress to weaker solutions until the most economical level of effective cleaning is obtained.
- 4 LOCTITE® 7840™ may attack painted surfaces in concentrations with less than 20 parts water.
- 5 **Note:** optimum performance occurs with stronger concentrations, dilution with warm water, agitation or scrubbing and extended surface contact.
- 6 **Caution:** cleaner residues may inhibit the cure of anaerobic products.

### Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

### Recommended Dilution Levels

Application	LOCTITE® 7840™ to water
Heavy cleaning and degreasing: dip tanks, washers	1:1 to 1:4
Medium cleaning and degreasing: fleet maintenance, siding, concrete floors, pressure sprayers, floor scrubbers, steam cleaners	1:16 to 1:32
Light cleaning: work areas, windows, walls, woodwork, furniture, carpets, counter tops	1:64 to 1:128

### Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labelling.

**Optimal Storage:** 8°C to 21°C. Storage below 8°C or greater than 28°C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Centre or Customer Service Representative.

### Conversions

(°C x 1.8) + 32 = °F	N/mm <sup>2</sup> x 145 = psi
kV/mm x 25.4 = V/mil	MPa x 145 = psi
mm / 25.4 = inches	N·m x 8.851 = lb·in
µm / 25.4 = mil	N·m x 0.738 = lb·ft
N x 0.225 = lb	N·mm x 0.142 = oz·in
N/mm x 5.71 = lb/in	mPa·s = cP