Flexiband

Jubilee's new band and buckle system called Flexiband further increases its range of clamping and banding solutions. It offers a high strength fastening solution.


Flexiband is ideal for strapping items securely and can commonly be seen in applications such as sign fixing where the tamper proof nature of the product is of paramount importance. The low profile of the buckle is useful where space is a consideration or where there is a snagging hazard. These benefits, combined with the corrosion resistance of 304 stainless steel means there is a wide range of industries where Jubilee Flexiband can be invaluable, including industrial, agriculture, automotive, civil engineering, marine, food, petrochemicals and offshore oil and gas to name a few.

Flexiband suits virtually any diameter and form and, if needed, can be double banded for extra strength.

Banding:-

| JUBILE | E JUBILEE | JUBILEE JUBILEE | | | | | |
|-------------|------------------------------------|------------------|----------------------|------------------------------|------------------------------|-------------|--|
| Part No. | Description | A Width mm | A Width Inches | S Band Thickness mm | Tensile Strength N/mm2 | Part No. | |
| FB09B | Banding in dispensers of 30 metres | 9 | ³ /8 | 0.65 | 540-750 | FB09B | |
| FB13B | Banding in dispensers of 30 metres | 13 | 1/2 | 0.75 | 540-750 | FB13B | |
| FB16B | Banding in dispensers of 30 metres | 16 | ⁵ /8 | 0.75 | 540-750 | FB16B | |
| FB19B | Banding in dispensers of 30 metres | 19 | 3/4 | 0.75 | 540-750 | FB19B | |

Buckles:-







Part No. FBT

| Part No. | Description | Width mm | Width Inches | Dimensions | | |
|-------------|--------------------------------|-------------|-----------------|------------|--------|--------|
| | | | | A = mm | B = mm | S = mm |
| FB09H | Buckles in boxes containing 25 | 9 | ³ /8 | 23 | 16 | 1.2 |
| FB13H | Buckles in boxes containing 25 | 13 | 1/2 | 35 | 27 | 1.4 |
| FB16H | Buckles in boxes containing 25 | 16 | ⁵ /8 | 38 | 27 | 1.4 |
| FB19H | Buckles in boxes containing 25 | 19 | 3/4 | 42 | 27 | 1.6 |

Corrosion Resistance: 1000 hours NSS Test

Fastening: Bend arms on buckle

Industry Recommendations:-



304 Stainless Steel



S